



YAMAUCHI



APRONS

APRONS for Spinning & Roving

Material 材料编号	Colour 颜色	Hardness 硬度 (Shore A)	Fibre 纤维	Features 特色
LM-55B	Light Grey 浅灰	55	Fine Count 细支纱 Cotton 棉	Soft Type, Anti-Cracking 防龟裂柔软型
LM-60Z	Grey 灰	60	Cotton 棉 Synthetic 化纤	Standard Type 标准型
MT-115B	Blue 蓝	62	Cotton 棉 Wool 羊毛 Synthetic 化纤	Anti-Cracking Type 防龟裂型
SOR	Dark Grey 深灰	65	Wool 羊毛 Synthetic 化纤	Oil Resistant Type 防油性型
TAJ-2	Black 黑	72	for MJS MJS 用	Abrasion Resistant Type 耐磨擦型
TAJ-17M	Brown 棕	70	for MVS MVS 用	Anti-Cracking Type 防龟裂型

APRONS for Glass Fiber



Material 材料编号	Colour 颜色	Hardness 硬度 (Shore A)	Fibre 纤维	Features 特色
FT72CSB	Black 黑	72	Glass Fibre 玻璃纤维	Surface roughness adjustable depending on yarn count 表面粗糙可 根据支纱调整


COTS for Spinning & Roving & Drawing

Material 材料编号	Colour 颜色	Hardness 硬度 (Shore A)	Fibre 纤维	Process 生产种类	Features 特色
620	Grey 灰	76 78 80 83	Cotton 棉 Synthetic 化纤	Spin 细纱 Rov 粗纱 Draw 并条	Standard Type 标准型
660	Green 青	80	Synthetic 化纤 Wool 羊毛	Spin 细纱 Draw 并条	High Grip Property 把持力特强型
660	Red 红	83	Synthetic 化纤 Wool 羊毛	Spin 细纱 Draw 并条	Abrasion Resistance 耐磨性型
770	Brown 茶	74	Synthetic 化纤 Wool 羊毛	Spin 细纱 Draw 并条	Soft Type 柔软型
103	Blue 蓝	80 83	Cotton 棉 Synthetic 化纤	Spin 细纱 Rov 粗纱 Draw 并条	Anti-Static 防静电
GS-63	Dark Green 深绿	63	Cotton 棉	Spin 细纱	Soft Type 柔软型
GS-70	Yellow 黄	70	Cotton 棉 P / C 涤棉	Spin 细纱	Soft Type 柔软型



Comber Detaching Roller

Material 材料编号	Colour 颜色	Hardness 硬度 (Shore A)	Fibre 纤维	Process 生产种类	Features 特色
2275	Yellow 黄	68	Cotton 棉	CM 梳棉	Special Double Layer Material 特别双层材质



DTY Products



APRON (TS-67A)

New apron "TS-67A" manufactured for false-twist and draw-texturing machines is developed to meet the demands of high-speed texturing systems and offers top-performance of yarn qualities, while exhibiting long maintenance cycles with high abrasion resistance.

新开发皮圈“TS-67A”具有高耐磨，高强度耐油与溶剂，表面硬度及磨擦系数适中，使用寿命长。高速转动中不抖动，不跑偏，表面磨擦系数适中，假捻效果强等特性。

Features 特性:

- High abrasion resistance 耐磨擦
- Toughness against chemicals 耐油与耐溶剂
- Excellent property against ozone-attack 优异的耐臭氧
- Minimize static build-up 抗静电
- Maximum yarn control 假捻效果强

COT (R25)

Rubber cot "R25" for DTY Nip-Roller have been employed for a long time owing to its superior physical properties.

"R25" has two types of construction; normal type and EFC (Easy Fit Cot) type, both with glue on inner surface. YAMAUCHI is able to offer three different hardness in "R-25" to meet the demands of yarn-speed for all customers.

R25拥有两种类型：普通型及EFC型，两种类型的内层有一层胶。为了应付不同速度的要求，山内可提供三种不同的硬度。

Features 特性:

- High abrasion resistance 耐磨擦
- High co-efficient of friction for yarn control 假捻效果强
- High crack resistance, especially by EFC type 防龟裂型
- Toughness against chemicals and oil 耐油与耐溶剂
- Lower static build-up 抗静电



Friction Disc for DTY

Durability with quality:

- After the long R&D and analysis of the world's friction discs, we, Yamauchi Corp., have succeeded in developing the polyurethane friction disc which has the maximum durability and at the same time, offers the stable yarn quality ie: tenacity, bulk and less yarn breakages.

新开发PU摩擦盘具有高耐磨, 高强度耐油与溶剂, 表面硬度及磨擦系数适中, 使用寿命长。适合纺各种旦数的弹力丝, 表面磨擦系数适中, 假捻效果强等特性。

- Above features also can solve the problems which you are facing by using ceramic discs.

以上特性可以解决发生在陶瓷片的问题。

- We are able to supply any size of friction discs, according to your requests.

尤其是外径, 可以根据客户的要求而生产各种规格来控制摩擦系数。

	Material 材质编号	Hardness 硬度 (Shore A)	Application 特色
	BH-90	90	Standard material providing the longest life. 使用寿命特久。 Durable against heavy denier POY. 持久及耐用
	BH-85	85	For more bulky yarn with low hardness without changing the present operating conditions. 低硬度, 适合于大量的高品质加弹丝。
	WT-90	90	Suitable for micro fibre with stable yarn quality for a long time. 适合于长期稳定及高品质的加弹丝。
	WT-85	85	To produce high quality micro filament yarn economically. 生产高品质的加弹丝。

■ **YAMAUCHI CORP.**

2-7, Shodai Tajika, Hirakata City Osaka, Japan

Tel: (072) 856 1132 Fax: (072) 856 6629

Email: textile@yamauchi.co.jp

Website: www.yamauchi.co.jp

■ **YAMAUCHI CORP. N.V**

Diepenbekerweg 1, B-3500 Hasselt, Belgium

Tel: (011) 233 061 Fax: (011) 235 969

Email: yama.bel@yamauchi.be

■ **YAMAUCHI (U.S.A.) CORPORATION**

5605 Seventy Seven Center Drive,

Suite 290 Charlotte, NC 28217 USA

TEL +1-704-527-4575 FAX +1-704-527-4577

Email ; yoshida@yamauchiusa.com

■ **YAMAUCHI (MALAYSIA) SDN. BHD.**

Plo 138, Senai Industrial Area Phase III, 81400 Senai,

Johor Darul Takzim, Malaysia

Tel: (07) 599 3335 Fax: (07) 599 3337

Email: ctsales@yamauchi.com.my

■ **YAMAUCHI (SEOUL OFFICE) CORPORATION**

8th F1, KFSB Bldg. 16-2, Yeoido-Dong,

Youngdongpo-ku, Seoul Korea

Tel: (02) 780 2658/9 Fax: (02) 782 9736

Email: yk2658@kornet.net